

EASY Top

Safety, quality, longevity

























EASY Top

Excellent price

EASY Top is the bar cover that combines functionality and top-quality finish. Designed to provide better protection for your pool, it can be used all year round.



Easy to use

The cover is rolled up from the right using a crank or effortlessly using the ROLLTROT^{2®} motor.

Quick and easy installation3 stainless steel tension pawls only to obtain a perfectly taut cover.

2 Extended life

located under the cover in line with the coping noses, bar passage PVC reinforcements and composite protective pads riveted under the

3 Leaf-proof and anti-lifting system along the lengths

and other impurities.

4 NEW Removable unrolling strap.

(Once the bar cover has been deployed, the strap can be stored).

5 Strap with stainless steel quick attachment system.

Finish

Strap welded along the lengths

SUPERBLACK Évolution fabric

Great resistance to abrasion and tearing. 100% opaque: prevents photosynthesis phenomenon. An Albigès exclusivity.

Economical solution

Less evaporation. Improved heat balance for longer, more affordable pool use. Cleaner water. An improvement on the solar cover, with its roller and the winterisation cover.

Warning

This cover is not a substitute for common It does not aim to replace the vigilance of parents and/or responsible adults, which remains the essential factor in the protection of young



*Full guarantee: See general conditions of sale.

DELIVERED WITH

- Stainless steel pawls.
- · Eyebolts.
- · Reinforced downgeared hand-wheel.
- NEW 1 removable unrolling strap.



COLOURS



Blue/SB Grey - Green/SB Grey - Amande/SB Grey - Grey/SB Grey - Dark Grey/SB Grey

OPTIONS

- · Eyebolt/sheath.
- Wooden deck stud.
- POLITPOT2®



•	KULLIKU	1-0			
					Palen
		9	ROLLTROT	- 76	
De	monstration			(.)	9

IDENTITY CARD				
ı	Fabric	Reinforced flexible PVC with a black polyester weft with grey underside coating.		
I	Weight	Fabric = 600 g/m^2 . Cover = 1.1 Kg/m^2 .		
	Breaking strength	2,500 N/5 cm (warp) and 2,000 N/5 cm (weft).		
	Tear strength	270 N (warp and weft direction).		
	Treatment	UV, cryptogamic and bacterial.		
I	Tube	1.5 μ, Ø 45 and 50 mm anodised aluminium.		
I	Overlaps	25 cm around the edge of the pool.		





Recommended retailer